

Contmark



Example of a data sheet/Name of the product/Image of the product



Denyo Generator DCA-400SPKII

Alternator Frequency Hz	50 / 60
Alternator Output Rating (kVA)	Continuous – 350 / 400, Standby – 385 / 440
Alternator No. Of Phases	3-Phase, 4-Wire
Alternator Rated Voltage V	2 Dual Voltage
Alternator Power Factor	0.8

Footer with contact address website, mail phone etc...



Alternator Voltage Regulation %	Within ± 1.5
Alternator Excitation	Brushless, Rotating, Exciter (With A.V.R)
Alternator Insulation	Class F
Engine Make & Model	Komatsu SA6D140-A
Engine Type	Inlined, Direct Injected, Turbocharge, Aftercooled
Engine Output Rating kW/min⁻¹	310/1500 / 357/1800
Engine No. of cylinders-Bore x Stroke mm	6 – 140 x 165
Engine Piston Displacement L	15.240
Engine Fuel	ASTM No. 2 Diesel Fuel or Equivalent
Engine Fuel consumption*2 L/h	52.1 / 60.8
Lube Oil Sump Capacity L	74

Contmark



Engine Coolant Capacity L	68.4
Engine Battery × Quantity	190H52x2 or. 210H52x2
Engine Fuel Tank Capacity L	490
Length mm	4200
Width mm	1400
Height mm	2100
Dry Weight (Full Weight) kg	5420
Sound Level 7m dB (A) 1500/1800 rpm (min⁻¹)*4	67.0 / 68.0